



**Ideal transport aid for application in damp or harsh environments such as meat or fish processing plants, dairies, pharmaceutical and chemical industry.**

## STAINLESS PALLET TRUCK

Stainless pallet truck		1KG=2.2LB 1INCH=25.4MM	
Item/Type		ACS20H	ACS20L
Capacity Q	kg	2000	2000
Min. fork height h	mm	85	75
Max. fork height h <sub>1</sub>	mm	200	190
Steering wheel	mm	Ø200x50	Ø180x50
Load roller Single	mm	Ø80x93	Ø74x93
Load roller Tandem	mm	Ø74x70	Ø74x70
Size of fork e*s	mm	160x60	
Width overall forks B	mm	520/540/685	
Fork length l	mm	1000/1100/1150/1220	

Conforms to EN 1757-2

- All metal parts made completely stainless steel, including hydraulic pump, fork frame, handle and so on.
- Ideal transport aid for application in damp or harsh environments such as meat or fish processing plants, dairies, pharmaceutical and chemical industry.
- With pressure relief valve and overload valve to prevent pump damages when loads exceeds weight limits.
- The enclosed fork tips (for Aisi316 stainless truck only) ensure there is no dead corner where corrosive spatters remains and damages the truck.
- Specially designed for applications where hygiene is of utmost importance.
- Nylon steering wheel and fork rollers as standard option for damp or harsh environments applications.



## GALVANIZED PALLET TRUCK

Galvanized pallet truck		1KG=2.2LB 1INCH=25.4MM	
Item/Type		ACZ20H	ACZ20L
Capacity Q	kg	2000	2000
Min. fork height h	mm	85	75
Max. fork height h <sub>1</sub>	mm	200	190
Steering wheel	mm	Ø200x50	Ø180x50
Load roller Single	mm	Ø80x93	Ø74x93
Load roller Tandem	mm	Ø80x70	Ø74x70
Size of fork e*s	mm	160x60	
Width overall forks B	mm	520/540/685	
Fork length l	mm	1100/1150/1220	

Conforms to EN 1757-2

- All the exposed parts of the whole truck galvanized, including hydraulic pump, fork frame, handle and so on.
- Special application in cold and wet environments resists the effects of cold, condensation and washing.
- Nylon steering wheel and fork rollers as standard option for damp or harsh environments applications.
- With pressure relief valve and overload valve to prevent pump damages when loads exceed weight limits.
- The one-piece pump design simplifies repairs, assuring reliable service and long life.

