

SCISSOR LIFT PALLET TRUCK

Scissor lift pallet truck design to load and unload conveyor, feed presses, or any applications requiring moving and positioning pallets or containers of materials.

- Equipped with quick lift function doubles the lift speed for loads lighter than 200kg.
- With pressure relief valve and overload valve to prevent pump damages when loads exceeds weight limits.
- The enclosed fork tips and reinforced fork frames ensures long service life.

Hand Scissor Lift Pallet Truck		1KG=2.2LB	1INCH=25.4MM	
ITEM \ TYPE		HLT10	HLT15	HLT(N)10
Capacity Q	Kg	1000	1500	1000
Min. fork height h	mm	85	85	85
Max. fork height h ₁	mm	800	800	800
Size of fork exs	mm	162x50	162x50	162x50
Length of fork l	mm	1140	1100	1150
Width overall fork (adjust/fixed) b5	mm	520/680	520/680	540/680
N.W.	Kg	105/112	118/125	128/133
Fork rollers	mm	Ø75x50	Ø75x50	Ø75x50
Big wheel	mm	Ø150x50	Ø150x50	Ø180x50
Dimension of wooden crate	mm	1930x590x720/ 1930x740x720	1930x590x720/ 1930x740x720	2040x600x1110/ 2040x740x1110
Pcs/20' container	mm	120/96	120/96	72/64

Note: HLT10&HLT15 is two-cylinder-system
HLT(N)10 is one-cylinder-system



ELECTRIC SCISSOR LIFT PALLET TRUCK

Powered by 12 voltage battery, driven by a good effective pump station. Used as both a work table and pallet truck 10-12 seconds pumping from the bottom to the top.



Electric Scissor Lift Pallet Truck					1KG=2.2LB	1INCH=25.4MM	
Model	Lifting Capacity(kg)	Lowest Fork Height(mm)	Max Fork Height(mm)	Fork Length X Fork Width(mm)			
DGB1500	1500	85	800	1100×520 1100×680			
DGB1000	1000	85	800	1140×520 1140×680			
		Dia. of front wheel(mm)	Dia. of rear wheel(mm)	Lifting time in full range(s)			Size of Fork(mm)
DGB1500		Ø75x50	Ø150x50	18			162×50
DGB1000		Ø75x50	Ø150x50	10/12			162×50
		Descending Speed(mm/s)	Motor working voltage(v)	Battery voltage(v)			Electricity volume(A/hour)
DGB1500		<0.1	12	12			63
DGB1000		<0.1	12	12			63
		Working pressure of Pump Station(Mpa)	Input/output voltage of Charger(v)	Max charging current of charger(A)			
DGB1500		21	AC230/115DC12	10			
DGB1000		15	200-240/12	10			

- Safety overload system prevents the truck from being used beyond its rated capacity.
- The handle automatically returns to its upright position when released.
- Lifting motor power 1.1KW.

TWO-CYLINDER SCISSOR LIFT PALLET TRUCK

With pressure relief valve and overload valve to prevent pump damages when loads exceeds weight limits.

Nylon steering wheel and fork rollers as standard option for damp or harsh environments applications.



Stainless Scissor Lifter			1KG=2.2LB	1INCH=25.4MM	
TYPE	SLP10	SLP15			
capacity	1000	1500			
fork width(W)	540	680			
fork length(L)	1150	1150			
min.fork height(H)	85	85			
Max. fork height	800	800			
front wheel	PU/Nylon 80*50				
rear wheel	PU/Nylon 180*50				
net weight	110	125			



- The INOX version of Scissor lift pallet truck is designed for corrosive environments or applications with high standards of hygiene where the goods need to be handled at a convenient working height.
- Ideal transport aid for application in damp or harsh environments such as meat or fish processing plants, dairies, pharmaceutical and chemical industry as transport aid as well as working table.

STAINLESS SCISSOR LIFT PALLET TRUCK

Stainless Scissor Lifter			1KG=2.2LB	1INCH=25.4MM	
TYPE	SLP10-INOX				
capacity	1000				
fork width(W)	540				
fork length(L)	1150				
min.fork height(H)	85				
Max. fork height	800				
front wheel	PU/Nylon 80*50				
rear wheel	PU/Nylon 180*50				
net weight	110				